

DRC-24V015W1RZ

Delta DIN Rail 24V/0.63A, Chrome II



■ Features:

- Class II, Double Isolation (No Earth connection is required)
- Supports universal AC input voltage and DC input voltage
- Mechanical dimensions are designed to meet DIN 43880 for building automation
- Low no load power consumption and compliance with DOE VI efficiency standard
- NEC Class 2 / Limited Power Source (LPS) certified
- Over Voltage Category III

ELECTRICAL SPECIFICATION

Output Voltage	24V DC
Rated Current	0.63
Power (W)	15
Dimming	No
AC input voltage range	Universal
Protection class	II
Inrush Current (typ.)	40A
IP protection level	IP20
Over Current / Overload protection	Type: auto-recovery.
Over Current / Overload protection (range)	101-150%
Over Temperature protection	Type: shut down output voltage. Re-power on to recovery.
Over Voltage protection	Type: shut down output voltage. Re-power on to recovery.
Over Voltage protection (range)	<36V
EMC Emission	EN55032
EMC Immunity	EN61000-4-2, -3, -4, -5, -6, -8, -11
Harmonic Current	Compliance to EN61000-3-3, EN61000-3-2, EN61000-3-3
Weight (kg)	0,06
Warranty	5 years
Mounting	DIN

Programmable	No
--------------	----

MECHANICAL SPECIFICATION