

POSC05200A-2555

Zasilacz POSC 5V/2A/10W, adapter czarny, gniazdo AC:CEE
7/16. wtyk 2.5x5.5mm prosty



ELECTRICAL SPECIFICATION

Housing type	Wertykalny
Output Voltage	5V DC
Rated Current	2A
Power (W)	10
Dimming	No
Voltage Ripple & Noise (max.)	120mVP-P
Line Regulation	± 5%
Load Regulation	± 5%
Setup, Rise Time	30ms
Hold up Time (typ.)	3ms
AC input voltage range	Universal
Protection class	II
PFC	No
Efficiency (typ.)	78,70%
AC Current (typ.)	0.4A
No Load Power Consumption (typ. / max.)	<0.10W
IP protection level	IP20
Over Current / Overload protection (range)	2.2A-4.0A
Over Current / Overload protection	Type: auto-recovery.
Short Circuit protection	Type: hiccup mode, auto-recovery.
Over Voltage protection	Type: shut down output voltage. Re-power on to recovery.

Working Temperature range	-5°C ÷ 40°C
Working Humidity range	5 ÷ 95% RH
Storage Temperature and Humidity	-40°C ÷ 85°C, 5 ÷ 90% RH
Safety Standards	Compliance to EN62368-1
Withstand Voltage	IN/OUT: 3.6kVAC
Isolation Resistance	IN/OUT: 50MQ/500VDC/25°C/70%
EMC Emission	Compliance to EN61000-3-3, Compliance to EN6100-3-2
EMC Immunity	EN 61000-4-3, EN 61000-4-4, EN 61000-4-5
Harmonic Current	Compliance to EN61000-3-2, EN61000-3-3
Dimmensions (L x W x H)	56.0 x 28.0 x 42.0mm
Weight (kg)	0.082
Warranty	3 years
Mounting	Wall mounted
DC Plug	2.5/5.5 mm
Programmable	No

MECHANICAL SPECIFICATION