

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**  
 Substance / mixture Varnish PVB 60 mixture  
 UFI RH20-M0YR-U00E-0J55
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
 Varnish for protecting PCBs  
**Mixture uses advised against**  
 The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**  
**Manufacturer**  
 Name or trade name AG TermoPasty Grzegorz Gąsowski  
 Address Kolejowa 33 E, Sokoły, 18-218 Poland  
 Identification number (CRN) 200133730  
 VAT number PL9661767714  
 Phone +48 86 274 13 42  
 Email msds@termopasty.pl  
 Web address www.termopasty.com
- Competent person responsible for the safety data sheet**  
 Name AG TermoPasty Grzegorz Gąsowski  
 Email msds@termopasty.pl
- 1.4. Emergency telephone number**  
 European emergency number: 112

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**  
 The mixture is classified as dangerous.

Flam. Liq. 2, H225  
 Skin Irrit. 2, H315  
 Eye Dam. 1, H318  
 STOT SE 3, H336

#### Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

#### Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye damage.

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

acetone  
 butan-1-ol

#### Hazard statements

|      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation.             |
| H318 | Causes serious eye damage.          |
| H336 | May cause drowsiness or dizziness.  |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

#### Precautionary statements

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P261           | Avoid breathing mist/vapours/spray.                                                                                              |
| P264           | Wash hands and exposed parts of the body thoroughly after handling.                                                              |
| P280           | Wear eye protection.                                                                                                             |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a doctor.                                                                                                       |
| P312           | Call a POISON CENTER if you feel unwell.                                                                                         |

#### Label elements for packages not exceeding 125 ml

##### Hazard pictogram



##### Signal word

Danger

##### Hazardous substances

acetone  
butan-1-ol

##### Hazard statements

H318 Causes serious eye damage.

##### Precautionary statements

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P280           | Wear eye protection.                                                                                                             |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a doctor.                                                                                                       |

#### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixture of substances and additives specified below.

**Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment**

| Identification numbers                                                                             | Substance name | Content in % weight | Classification according to Regulation (EC) No 1272/2008              | Note |
|----------------------------------------------------------------------------------------------------|----------------|---------------------|-----------------------------------------------------------------------|------|
| Index: 606-001-00-8<br>CAS: 67-64-1<br>EC: 200-662-2<br>Registration number: 01-2119471330-49-XXXX | acetone        | 50-75               | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066 | 1    |
| Index: 603-117-00-0<br>CAS: 67-63-0<br>EC: 200-661-7<br>Registration number: 01-2119457558-25-XXXX | isopropanol    | ≤20                 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336           | 1    |

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Varnish PVB 60

Creation date 17th October 2022 Version 14.0  
Revision date 30th January 2026

| Identification numbers                                                                                | Substance name | Content in % weight | Classification according to Regulation (EC) No 1272/2008                                                     | Note |
|-------------------------------------------------------------------------------------------------------|----------------|---------------------|--------------------------------------------------------------------------------------------------------------|------|
| Index: 603-004-00-6<br>CAS: 71-36-3<br>EC: 200-751-6<br>Registration number:<br>01-2119484630-38-XXXX | butan-1-ol     | ≤20                 | Flam. Liq. 3, H226<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>STOT SE 3, H335, H336 | 1    |

### Notes

1 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

#### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water/shower.

#### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

#### If swallowed

DO NOT INDUCE VOMITING! Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

### 4.2. Most important symptoms and effects, both acute and delayed

#### If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause drowsiness or dizziness.

#### If on skin

Causes skin irritation.

#### If in eyes

Causes serious eye damage.

#### If swallowed

Corrosion of the digestion system can occur.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### Unsuitable extinguishing media

Water - full jet.

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Use only non-sparking tools. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

| Content | Packaging type | Material of package |
|---------|----------------|---------------------|
| 1 l     | jerry can      | FE                  |
| 50 ml   | bottle         | HDPE                |

#### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

#### 7.3. Specific end use(s)

not available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### European Union

#### Commission Directive 2000/39/EC

| Substance name (component) | Type        | Value                  |
|----------------------------|-------------|------------------------|
| acetone (CAS: 67-64-1)     | OEL 8 hours | 1210 mg/m <sup>3</sup> |
|                            | OEL 8 hours | 500 ppm                |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

#### United Kingdom

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

| Substance name (component) | Type      | Value                  |
|----------------------------|-----------|------------------------|
| acetone (CAS: 67-64-1)     | WEL 8h    | 1210 mg/m <sup>3</sup> |
|                            | WEL 8h    | 500 ppm                |
|                            | WEL 15min | 3620 mg/m <sup>3</sup> |
|                            | WEL 15min | 1500 ppm               |
| isopropanol (CAS: 67-63-0) | WEL 8h    | 999 mg/m <sup>3</sup>  |
|                            | WEL 8h    | 400 ppm                |
|                            | WEL 15min | 1250 mg/m <sup>3</sup> |
|                            | WEL 15min | 500 ppm                |

#### United Kingdom

#### EH40/2005 Workplace exposure limits (Fourth Edition 2020)

| Substance name (component) | Type      | Value                 |
|----------------------------|-----------|-----------------------|
| butan-1-ol (CAS: 71-36-3)  | WEL 15min | 154 mg/m <sup>3</sup> |
|                            | WEL 15min | 50 ppm                |

#### Notes

Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

#### DNEL

| acetone             |                   |                        |                          |
|---------------------|-------------------|------------------------|--------------------------|
| Workers / consumers | Route of exposure | Value                  | Effect                   |
| Workers             | Inhalation        | 2420 mg/m <sup>3</sup> | Acute effects local      |
| Workers             | Dermal            | 186 mg/kg bw/day       | Chronic effects systemic |
| Workers             | Inhalation        | 1210 mg/m <sup>3</sup> | Chronic effects systemic |
| Consumers           | Dermal            | 62 mg/kg bw/day        | Chronic effects systemic |
| Consumers           | Inhalation        | 200 mg/m <sup>3</sup>  | Chronic effects systemic |
| Consumers           | Oral              | 62 mg/kg bw/day        | Chronic effects systemic |

| butan-1-ol          |                   |                      |                          |
|---------------------|-------------------|----------------------|--------------------------|
| Workers / consumers | Route of exposure | Value                | Effect                   |
| Workers             | Inhalation        | 10 mg/m <sup>3</sup> | Chronic effects systemic |
| Consumers           | Inhalation        | 55 mg/m <sup>3</sup> | Chronic effects systemic |
| Consumers           | Oral              | 3.125 mg/kg          | Chronic effects systemic |

| isopropanol         |                   |                       |                          |
|---------------------|-------------------|-----------------------|--------------------------|
| Workers / consumers | Route of exposure | Value                 | Effect                   |
| Workers             | Inhalation        | 500 mg/m <sup>3</sup> | Chronic effects systemic |
| Workers             | Dermal            | 888 mg/kg bw/day      | Chronic effects systemic |
| Consumers           | Inhalation        | 89 mg/m <sup>3</sup>  | Chronic effects systemic |
| Consumers           | Dermal            | 319 mg/kg bw/day      | Chronic effects systemic |
| Consumers           | Oral              | 26 mg/kg bw/day       | Chronic effects systemic |

#### PNEC

| acetone           |           |
|-------------------|-----------|
| Route of exposure | Value     |
| Drinking water    | 10.6 mg/l |
| Marine water      | 1.06 mg/l |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

| acetone                            |                                         |
|------------------------------------|-----------------------------------------|
| Route of exposure                  | Value                                   |
| Sea sediments                      | 30.4 mg/kg of dry substance of sediment |
| Freshwater sediment                | 30.4 mg/kg of dry substance of sediment |
| Soil (agricultural)                | 29.5 mg/kg of dry substance of soil     |
| Microorganisms in sewage treatment | 100 mg/l                                |

| butan-1-ol                   |                                      |
|------------------------------|--------------------------------------|
| Route of exposure            | Value                                |
| Drinking water               | 0.082 mg/l                           |
| Marine water                 | 0.0082 mg/l                          |
| Water (intermittent release) | 2.25 mg/l                            |
| Freshwater sediment          | 0.178 mg/kg                          |
| Sea sediments                | 0.0178 mg/kg                         |
| Soil (agricultural)          | 0.015 mg/kg of dry substance of soil |

| isopropanol            |                            |
|------------------------|----------------------------|
| Route of exposure      | Value                      |
| Drinking water         | 140.9 mg/l                 |
| Marine water           | 140.9 mg/l                 |
| Freshwater sediment    | 552 mg/kg of dry substance |
| Freshwater environment | 552 mg/kg of dry substance |
| Soil (agricultural)    | 28 mg/kg of dry substance  |

#### 8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

##### Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

##### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

##### Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

##### Thermal hazard

Data not available.

##### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                          |                                     |
|----------------------------------------------------------|-------------------------------------|
| Physical state                                           | liquid                              |
| Colour                                                   | data not available                  |
| Odour                                                    | characteristic                      |
| Melting point/freezing point                             | data not available                  |
| Boiling point or initial boiling point and boiling range | >35 °C                              |
| Flammability                                             | Highly flammable liquid and vapour. |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

|                                                   |                         |
|---------------------------------------------------|-------------------------|
| Lower and upper explosion limit                   | data not available      |
| Flash point                                       | data not available      |
| Auto-ignition temperature                         | data not available      |
| Decomposition temperature                         | data not available      |
| pH                                                | data not available      |
| Kinematic viscosity                               | data not available      |
| Solubility in water                               | data not available      |
| Solubility in fats                                | data not available      |
| Partition coefficient n-octanol/water (log value) | data not available      |
| Vapour pressure                                   | data not available      |
| Density and/or relative density                   |                         |
| Density                                           | 0.792 g/cm <sup>3</sup> |
| Relative vapour density                           | data not available      |
| Particle characteristics                          | data not available      |
| Form                                              | liquid                  |

#### 9.2. Other information

|                      |                    |
|----------------------|--------------------|
| Evaporation rate     | data not available |
| Ignition temperature | 38 °C              |

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

not available

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

#### Acute toxicity

Based on available data the classification criteria are not met.

| acetone            |                  |                         |               |                                        |     |
|--------------------|------------------|-------------------------|---------------|----------------------------------------|-----|
| Route of exposure  | Parameter        | Value                   | Exposure time | Species                                | Sex |
| Oral               | LD <sub>50</sub> | 5800 mg/kg              |               | Rat (Rattus norvegicus)                |     |
| Inhalation (vapor) | LC <sub>50</sub> | 76000 mg/m <sup>3</sup> | 4 hours       | Rat (Rattus norvegicus)                |     |
| Dermal             | LD <sub>50</sub> | 7400 mg/kg              |               | Rabbit                                 |     |
| Dermal             | LD <sub>50</sub> | 7400 mg/kg              |               | Guinea-pig (Cavia aperea f. porcellus) |     |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

| butan-1-ol        |                  |            |               |                         |     |
|-------------------|------------------|------------|---------------|-------------------------|-----|
| Route of exposure | Parameter        | Value      | Exposure time | Species                 | Sex |
| Oral              | LD <sub>50</sub> | 2292 mg/kg |               | Rat (Rattus norvegicus) |     |
| Dermal            | LD <sub>50</sub> | 3430 mg/kg |               | Rabbit                  |     |
| Inhalation        | LC <sub>50</sub> | 17.76 mg/l | 4 hours       | Rat (Rattus norvegicus) |     |

| isopropanol       |                  |             |               |         |     |
|-------------------|------------------|-------------|---------------|---------|-----|
| Route of exposure | Parameter        | Value       | Exposure time | Species | Sex |
| Inhalation        | LC <sub>50</sub> | >5 mg/l     | 4 hours       | Rat     |     |
| Oral              | LD <sub>50</sub> | >2000 mg/kg |               | Rat     |     |
| Skin              | LD <sub>50</sub> | >2000 mg/kg |               | Rabbit  |     |

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye damage.

| acetone           |        |          |               |         |
|-------------------|--------|----------|---------------|---------|
| Route of exposure | Result | Method   | Exposure time | Species |
| Eye               |        | OECD 405 |               |         |

#### Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data the classification criteria are not met.

#### Carcinogenicity

Based on available data the classification criteria are not met.

#### Reproductive toxicity

Based on available data the classification criteria are not met.

#### Toxicity for specific target organ - single exposure


May cause drowsiness or dizziness.

#### Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

#### Aspiration hazard

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. Based on available data the classification criteria are not met.



## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

##### Other information

not available

## SECTION 12: Ecological information

### 12.1. Toxicity

not available

#### Acute toxicity

| acetone          |            |               |                                |             |
|------------------|------------|---------------|--------------------------------|-------------|
| Parameter        | Value      | Exposure time | Species                        | Environment |
| LC <sub>50</sub> | 8800 mg/l  | 48 hours      | Invertebrates                  | Fresh water |
| LC <sub>50</sub> | 2100 mg/l  | 24 hours      | Invertebrates                  | Salt water  |
| LOEC             | 530 mg/l   | 8 days        | Algae and other aquatic plants | Fresh water |
| NOEC             | 430 mg/l   | 96 hours      | Algae and other aquatic plants | Salt water  |
| LC <sub>50</sub> | 5540 mg/l  | 96 hours      | Fish (Oncorhynchus mykiss)     | Fresh water |
| LC <sub>50</sub> | 11000 mg/l | 96 hours      | Fish                           | Salt water  |

| butan-1-ol       |           |               |                                                                  |             |
|------------------|-----------|---------------|------------------------------------------------------------------|-------------|
| Parameter        | Value     | Exposure time | Species                                                          | Environment |
| LC <sub>50</sub> | 1376 mg/l | 96 hours      | Fish (Pimephales promelas)                                       |             |
| EC <sub>50</sub> | 1328 mg/l | 48 hours      | Daphnia (Daphnia magna)                                          |             |
| EC <sub>50</sub> | 4390 mg/l | 17 hours      | Microorganisms (Pseudomonas putida)                              |             |
| EC <sub>50</sub> | 225 mg/l  | 96 hours      | Algae and other aquatic plants (Pseudokirchneriella subcapitata) |             |
| NOEC             | 4.1 mg/l  | 21 days       | Daphnia (Daphnia magna)                                          |             |
| EC <sub>50</sub> | 18 mg/l   | 21 days       | Daphnia (Daphnia magna)                                          |             |

| isopropanol      |            |               |                                 |             |
|------------------|------------|---------------|---------------------------------|-------------|
| Parameter        | Value      | Exposure time | Species                         | Environment |
| LC <sub>50</sub> | 9640 mg/l  | 96 hours      | Fish                            |             |
| EC <sub>50</sub> | 13299 mg/l | 48 hours      | Crustaceans                     |             |
| EC <sub>50</sub> | 1000 mg/l  | 72 hours      | Algae (Scenedesmus subspicatus) |             |

#### Chronic toxicity

| acetone   |           |               |                               |             |
|-----------|-----------|---------------|-------------------------------|-------------|
| Parameter | Value     | Exposure time | Species                       | Environment |
| NOEC      | 2212 mg/l | 24 hours      | Invertebrates (Daphnia magna) |             |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

#### 12.2. Persistence and degradability

Data not available.

#### 12.3. Bioaccumulative potential

Data not available.

#### 12.4. Mobility in soil

Data not available.

#### 12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

#### 12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

#### 12.7. Other adverse effects

Data not available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Packaging waste type code

15 01 02 plastic packaging

15 01 10\* packaging containing residues of or contaminated by hazardous substances

(\*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

### SECTION 14: Transport information

#### 14.1. UN number or ID number

UN 1993

#### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Acetone)

#### 14.3. Transport hazard class(es)

3 Flammable liquids

#### 14.4. Packing group

III

#### 14.5. Environmental hazards

not relevant

#### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

#### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

### Additional information

Hazard identification No.

30

UN number

1993

Classification code

F1

Safety signs

3



### Road transport - ADR

Special provisions

274, 601

Limited quantities

5 L

Excepted quantities

E1

#### Packaging

Packing instructions

P001, IBC03, LP01, R001

Mixed packing provisions

MP19

#### Portable tanks and bulk containers

Guidelines

T4

Special provisions

TP1, TP29

#### ADR tank

Tank code

LGBF

Vehicles for tank carriage

FL

Transport category

3

Tunnel restriction code

(D/E)

#### Special provision for

packages

V12

operation

S2

### Railway transport - RID

Special provisions

274, 601

Excepted quantities

E1

#### Packaging

Packing instructions

P001, IBC03, LP01, R001

Mixed packing provisions

MP19

#### Portable tanks and bulk containers

Guidelines

T4

Special provisions

TP1, TP29

#### RID Tanks

Tank code

LGBF


Transport category

0

#### Special provision for

packages

W12



# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

|        |                                                       |
|--------|-------------------------------------------------------|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H225   | Highly flammable liquid and vapour.                   |
| H226   | Flammable liquid and vapour.                          |
| H302   | Harmful if swallowed.                                 |
| H315   | Causes skin irritation.                               |
| H318   | Causes serious eye damage.                            |
| H319   | Causes serious eye irritation.                        |
| H335   | May cause respiratory irritation.                     |
| H336   | May cause drowsiness or dizziness.                    |

#### Guidelines for safe handling used in the safety data sheet

|                |                                                                                                                                  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------|
| P280           | Wear eye protection.                                                                                                             |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a doctor.                                                                                                       |
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P261           | Avoid breathing mist/vapours/spray.                                                                                              |
| P264           | Wash hands and exposed parts of the body thoroughly after handling.                                                              |
| P312           | Call a POISON CENTER if you feel unwell.                                                                                         |

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

|                  |                                                                                                   |
|------------------|---------------------------------------------------------------------------------------------------|
| Acute Tox.       | Acute toxicity                                                                                    |
| ADR              | Agreement concerning the international carriage of dangerous goods by road                        |
| BCF              | Bioconcentration Factor                                                                           |
| CAS              | Chemical Abstracts Service                                                                        |
| CLP              | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures |
| EC               | Identification code for each substance listed in EINECS                                           |
| EC <sub>50</sub> | Concentration of a substance when it is affected 50 % of the population                           |
| EINECS           | European Inventory of Existing Commercial Chemical Substances                                     |
| EmS              | Emergency Response Procedures for Ships Carrying Dangerous Goods                                  |
| EU               | European Union                                                                                    |
| EuPCS            | European Product Categorisation System                                                            |
| Eye Dam.         | Serious eye damage                                                                                |
| Eye Irrit.       | Eye irritation                                                                                    |
| Flam. Liq.       | Flammable liquid                                                                                  |
| IATA             | International Air Transport Association                                                           |

## SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

### Varnish PVB 60

|               |                   |         |      |
|---------------|-------------------|---------|------|
| Creation date | 17th October 2022 | Version | 14.0 |
| Revision date | 30th January 2026 |         |      |

|                     |                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------|
| IBC                 | International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals       |
| ICAO                | International Civil Aviation Organization                                                         |
| IMDG                | International Maritime Dangerous Goods                                                            |
| IMO                 | International Maritime Organization                                                               |
| INCI                | International Nomenclature of Cosmetic Ingredients                                                |
| ISO                 | International Organization for Standardization                                                    |
| IUPAC               | International Union of Pure and Applied Chemistry                                                 |
| LC <sub>50</sub>    | Lethal concentration of a substance in which it can be expected death of 50% of the population    |
| LD <sub>50</sub>    | Lethal dose of a substance in which it can be expected death of 50% of the population             |
| log K <sub>ow</sub> | Octanol-water partition coefficient                                                               |
| NOEC                | No observed effect concentration                                                                  |
| OEL                 | Occupational Exposure Limits                                                                      |
| PBT                 | Persistent, bioaccumulative and toxic                                                             |
| PMT                 | Persistent, mobile and toxic                                                                      |
| ppm                 | Parts per million                                                                                 |
| REACH               | Registration, Evaluation, Authorisation and Restriction of Chemicals                              |
| RID                 | Regulation concerning the International Carriage of Dangerous Goods by Rail                       |
| Skin Irrit.         | Skin irritation                                                                                   |
| STOT SE             | Specific target organ toxicity - single exposure                                                  |
| UN number           | Four-figure identification number of the substance or article taken from the UN Model Regulations |
| UVCB                | Substances of unknown or variable composition, complex reaction products or biological materials  |
| VOC                 | Volatile organic compounds                                                                        |
| vPvB                | Very persistent and very bioaccumulative                                                          |
| vPvM                | Very persistent and very mobile                                                                   |

#### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

#### Recommended restrictions of use

not available

#### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

#### The changes (which information has been added, deleted or modified)

The version 14.0 replaces the SDS version from Friday, 17 January 2025. Changes were made in sections 2, 13 and 16.

#### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.