

Dry TF grease

Versatile lubricant, ideal for demanding industrial and household applications. Thanks to its unique formula based on pure Teflon (PTFE), the product offers exceptional anti-adhesive properties, an extremely low coefficient of friction, and protection against contaminants. It is the perfect solution for environments where cleanliness and operational efficiency are crucial.

Product features:

- ✓ versatility of applications,
- ✓ prevents adhesion of dirt, dust, and other contaminants,
- ✓ provides protection against water, oils, and chemicals,
- ✓ leaves a dry and clean coating,
- ✓ 360° valve for easy application.

Applications:

- ✓ vacuum forming or plastic extrusion,
- ✓ gear wheels, gears, bearings,
- ✓ rails and sliding guides,
- ✓ belt, roller, and sliding conveyors,
- ✓ timing belts, chains, bearings, ropes,
- ✓ locks, connectors, pedals, window fittings, door hinge pins,
- ✓ cutting tools.

Physicochemical properties

Appearance	White gas
Odor	Characteristic
Density at 20°C	2.15 g/cm ³
Operating temperature range	-40°C to 250°C
Solubility in water	Does not dissolve
Shelf life	3 years



Compatibility:

Dry TF grease It is safe for most materials, including metals, plastics, and rubber. Its dry coating protects surfaces from damage while ensuring smooth and precise operation even under challenging conditions.

Application method

Aerosol with tube	Yes
-------------------	-----

Usage instructions:

Restricted to professional users. Read safety data sheet carefully prior to use.

Before application, make sure the surface is clean and dry. Shake the aerosol before use to ensure even distribution of the components. Point the applicator with the precision tube at the selected surface and spray, applying an even, thin layer of lubricant. Thanks to the 360° valve, the product can be applied in any position, making it easier to work in hard-to-reach areas. After application, wait a moment for the lubricant to evaporate and form a dry, protective coating.

Package

Aerosol	100 ml (ART.AGT-165) - 12 pcs.* 400 ml (ART.AGT-178) - 4/12 pcs.*
---------	--

*Quantity of pcs. in a bulk package.

Storage:

Store in closed containers, in dry, well-ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Technical support:

AG TermoPasty provides technical support, answering questions about the technical specifications and applications of our products. Please contact us via email at info@termopasty.pl.

Note:

The data presented in this document reflect our current state of knowledge and describe the typical properties and applications of the product. However, the responsibility for determining the suitability of this product for specific applications lies with the user. AG TermoPasty is not liable for the results of the product's use, as the conditions of its application are beyond our control.